



SCHEDULE

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Light Loss Factor	Wattage
	PL1	6	Lithonia Lighting	DSX1 LED P1 30K BLC4 VOLTAGE MOUNTING CONTROL OTHER FINISH	DSX1 TYPE IV BACKLIGHT CONTROL MOUNTED @ 16'-0" AFF *ADVISE POLE*	0.9	50.9
	WP1	3	Lithonia Lighting	WDGE2 P2 30K 70CRI T2M VOLTAGE MOUNTING OPTIONS FINISH	WDGE2 TYPE II MEDIUM WALL MOUNTED @ 12'-0" AFF	0.9	18.9815

STATISTICS

DESCRIPTION	SYMBOL	AVG.	MAX	MIN.	MAX/MIN	AVG/MIN
GROUND	+	0.1 fc	0.5 fc	0.0 fc	N/A	N/A
PAVEMENT	+	1.3 fc	3.0 fc	0.1 fc	30.0:1	13.0:1

NOTES:

-REFLECTANCES ASSUMED:
WALL: 50
FLOOR: 20

- MOUNTING HEIGHTS:
PL1: 16'-0"
WP1: 12'-0"

- TASK HEIGHT: 0" ABOVE GRADE
- CALCULATION POINT SPACING: 10'X10'
OC

Plan View
Scale - 1" = 9ft

Planning Received 5/5/25

DISCLAIMER:

-THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES ONLY AND ARE NOT INTENDED FOR CONSTRUCTION. VALUES REPRESENTED ARE AN APPROXIMATION GENERATED FROM MANUFACTURERS PHOTOMETRIC IN-HOUSE OR INDEPENDANT LAB TEST WITH DATA SUPPLIED BY LAMP MANUFACTURERS.